RIDGE VENT 9" Filtered Shingle-Over Ridge Vent

CertainTeed® Ridge Vent

CertainTeed Ridge Vent installs on the peak of the roof, allowing exhaust ventilation along the entire ridge, end-to-end. With a 9" width, matching shingles can be installed over the vent, allowing the vent to appear almost invisible from the ground. Intake vents must be installed to provide proper airflow.

CertainTeed Ridge Vents combined with sufficient intake vents, such as CertainTeed Intake Vent, are the most efficient and effective systems you can install.



FEATURES AND BENEFITS

- Designed with an external baffle to deflect wind and weather over the vent to help protect the attic from rain and snow infiltration. The external baffle creates low pressure over the vent openings to "pull" air from the attic
- Internal weather filter provides a more complete barrier to help protect the attic from wind-driven rain, snow, dust and insects
- Easy installation has pre-printed slot guides for truss or ridge pole construction. Pre-drilled nail holes are designed to assure proper nailing
- 16" sq. of net free area per linear foot
- CertainTeed Ridge Vent is pre-formed to a 4/12 pitch, and fits pitches from 3/12 to 12/12
- Limited Lifetime Warranty and 5-Year SureStart™ Protection
- Ten 4' pieces per box / Weight: 19 lbs. Part #95989 / Model #SHFV9CC Color: Charcoal

- Works year-round to ventilate the attic
- Provides evenly distributed ventilation along the entire underside of the roof
- Slim design for visual appeal
- Provides a higher volume of airflow per square foot of attic area than any other fixed-vent system
- Design maximizes airflow across the entire underside of roof sheathing
- Changes in wind direction have no significant effect on vent performance

ShingleVent II-9 (CertainTeed Ridge Vent) is Manufactured for CertainTeed Corporation by Air Vent, Inc., Orrick, MO.



Imprinted slot guides for _ proper slot width

Highest quality co-polymer remains sturdy, nailable and flexible in all climates

Reinforced ribs for greater stability and rigidity

Built-in ventilating end plug seals the end

Cap shingles install easily making the vent virtually invisible • Nail holes located at 16" and 24" centers

Nail bosses, reinforced nail holes designated to prevent over nailing

Weather filter provides advanced protection from rain, snow, dust and insect intrusion

High gloss nailing lines for accurate, fast cap shingle nailing

Air slots have 16" sq. free vent area per linear ft.

External wind baffle creates low air pressure and helps pull air out of the attic



CertainTeed Corporation

ROOFING • SIDING • TRIM • DECKING • RAILING • FENCE • GYPSUM • CEILINGS • INSULATION 20 Moores Road Malvern, Pa 19355 Professional: 800-233-8990 Consumer: 800-782-8777 certainteed.com